

Product equivalence for North America

6mm Glass | 13mm Spacer (Argon 90% Air 10%) | 6mm Glass

Triple Silver Solar Control									
VLT Range	Manufacturer	Solar Control and Low-e Coating Description	Face of Coating	VLT (%)	Reflectance OUT (%)	Reflectance IN (%)	Winter U-value (Btu/h.ft ² .F)	SHGC	LSG
60%	Saint-Gobain	Cool-Lite XTREME 61/29	2	60	11	14	0.24	0.26	2.31
	Guardian	SNX 62/27	2	62	11	12	0.24	0.27	2.30
	Cardinal	LoE 366	2	62	11	12	0.24	0.28	2.21
	AGC	Energy Select 28	2	62	13	14	0.24	0.28	2.21
	Vitro PPG	Solarban 72	2	66	13	14	0.24	0.27	2.44
	Vitro PPG	Solarban 70XL	2	64	12	13	0.24	0.27	2.37
	Viracon	VNE1-63	2	62	10	11	0.24	0.29	2.14

Double Silver Solar Control									
70%	Saint-Gobain	Cool-Lite SKN 176 II	2	69	13	15	0.24	0.33	2.09
	Guardian	SN 68	2	68	11	12	0.24	0.38	1.79
	Cardinal	LoE 272	2	70	11	11	0.24	0.40	1.75
	Cardinal	LoE 270	2	68	12	13	0.24	0.36	1.89
	Pilkington	Suncool 70/35	2	70	15	15	0.24	0.36	1.94
	Pilkington	Suncool 66/35	2	66	18	19	0.24	0.34	1.94
	AGC	Energy Select 40	2	69	12	12	0.24	0.39	1.77
	AGC	Energy Select 36	2	65	14	16	0.24	0.36	1.81
	Vitro PPG	Solarban 60	2	70	11	12	0.24	0.39	1.79
	Viracon	(Viracon) VE1-2M	2	70	11	12	0.24	0.38	1.84